



Key Features

- ▶ **Real time output of TEC and iono scintillation indices on all GNSS L-band frequencies**
- ▶ **100 Hz unfiltered correlation output for in-depth scintillation analysis**
- ▶ **Full compatibility with common scintillation and TEC monitoring file formats**
- ▶ **100 Hz code, phase and intensity output with user controlled noise bandwidth**
- ▶ **Unique interference monitoring and mitigation (AIM+)**
- ▶ **Powerful Web UI and logging tools**
- ▶ **Rugged housing and multiple interfaces**

The PolaRx5S is the world's leading ionospheric GNSS receiver. With 544 channels, it provides I&Q correlations, phase, code and carrier-to-noise at up to 100 Hz for all GNSS L-band frequencies.

Space Weather Applications

The PolaRx5S outputs an extensive set of GNSS measurements and iono-indices, including I&Q correlation, phase and intensity, up to 100 Hz. Featuring an ultra-low noise oscillator, it enables precise phase scintillation monitoring with a phase noise standard deviation (Φ_{60}) as low as 0.03 rad.

GNSS+™ Technology

The A Posteriori Multipath Estimator (APME+), unique in its ability to tackle short-delay multipath, enhances the measurement quality while LOCK+ tracking guarantees robust tracking of rapid signal dynamics during scintillation events.

Radio interferences events, more and more present, are difficult to differentiate from scintillation events. The PolaRx5S incorporates advanced interference mitigation techniques to suppress interference before it can affect the iono indices.

Networking, remote operation, and data logging

Communication and (remote) management of the PolaRx5S is made easy with a powerful built-in Web UI accessible over WiFi, network or USB connection. The Web UI features secured access to all receiver settings and status information, data storage, and fast and robust firmware upgrading.

SBF, RINEX and BINEX data logging is possible on both a built-in 16 GB memory and on an externally connected device. Up to 24 independent data archives can be defined. Logged data can be accessed via the web UI server or automatically pushed to a FTP server.

FEATURES

GNSS Technology

544 hardware channels for simultaneous tracking of all visible satellite signals

Supported signals: GPS (L1P, L1 C/A, L2, L5) GLONASS (L1, L2, L3) GALILEO (E1, E5ab, AltBoc, E6), BEIDOU (B1, B2, B3), SBAS (L1, L5), IRNSS (L5), QZSS (L1, L2, L5) (Galileo, BeiDou and IRNSS are optional features)

P-code tracking on GPS and GLONASS L1 and L2 to avoid CA-P biases

Up to 100 Hz raw data output (code, carrier, CN0, navigation data)

Unfiltered correlation output

A Posteriori Multipath Estimator (APME+) including code and phase multipath mitigation

AIM+ interference mitigates against wide and narrow band interference

Spectrum analyser

All multipath mitigation and smoothing algorithms can be enabled/disabled

Formats

ISMR (Ionospheric Scintillation Monitoring Record)

Septentrio Binary Format (SBF), fully documented with sample parsing tools

RINEX (obs, nav, meteo) v2.x, 3.x

BINEX

NMEA v2.30 and v4.10 output format

RTCM output (all MSM messages supported)

Connectivity

x PPS output (max 100 Hz)

10 MHz reference output

4 hi-speed serial ports

1 Ethernet port (100 MBps)

Integrated WiFi (802.11 b/g/n)

Power Over Ethernet

1 full speed USB port

1 USB host for external disk

16 GB standard on-board logging

Up to 24 parallel data records

Advanced Web UI providing all receiver controls and status monitoring

FTP server, FTP push, SFTP

Ntrip (server, caster)

RxTools, intuitive GUI tools for receiver monitoring, data conversion and analysis

PERFORMANCE

Measurement precision

Phase noise bandwidth 1 - 50 Hz
(configurable)

Phi60 noise floor 0.03 rad

Iono-indices¹

- S4
- Phi01, Phi03, Phi10, Phi30, Phi60
- Code-Carrier divergence (CCD)
- Scintillation Intensity (SI)
- Phase spectrum slope and strength at 1 Hz (p&T)

TEC

- Corrected for satellite biases²
- Calibration tool for receiver+antenna biases
- User-selectable signal combination
- No need for CA-P calibration table

Update

Code, phase, intensity, correlations 100 Hz

Iono indices and TEC 60 s

Tracking performance (C/N0 threshold)³

Tracking 20 db-Hz

Acquisition 33 db-Hz



PHYSICAL AND ENVIRONMENTAL

Size 284 x 140 x 37 mm
(11.18 x 5.51 x 1.45 in)

Weight 1.06 kg (2.33 lb)

Input voltage 9 – 30 VDC

Antenna LNA Power Output

Output voltage +5 VDC

Maximum current 200 mA

Power Consumption 3.5 - 5.7 W

Operating temperature -40 °C to +65 °C
(-40 °F to +149 °F)

Storage temperature -40 °C to +85 °C
(-40 °F to +185 °F)

Humidity 5 % to 95 % (non-condensing)

Connectors

Antenna TNC female

REF OUT BNC female

PPS OUT BNC female

Power ODU 3 pins female

COM1 ODU 7 pins female

COM2 ODU 7 pins female

COM3/4/USB ODU 7 pins female

USB Host ODU 5 pins female

IN ODU 7 pins female

OUT ODU 5 pins female

Ethernet ODU 4 pins

WiFi Antenna SMA female

Certification IP65, RoHS, CE FCC
Class B Part 15

¹ 3 carriers per satellite

² If transmitted by the satellite

³ Depends on user settings of tracking loops parameters

Europe
Greenhill Campus
Interleuvenlaan 15i
3001 Leuven, Belgium
+32 16 30 08 00

Americas
Suite 200,
23848 Hawthorne Blvd
Torrance, CA 90505, USA
+1 310 541 8139

Asia-Pacific
Level 901, The Lee Gardens
33 Hysan Avenue
Causeway Bay, Hong Kong
+852 3959 8680

